



FullTech Hotmelt Gun Hot Spray-Slot Gun for Hotmelt Glue

FullTech Hotmelt Gun is an electrically heated and pneumatically actuated flow gun for the processing of hotmelt glues in block and granulates form. The glue can be extruded in spray,rope (bead) or dot form. Overhead working is not possible. Temperature controller and Air Pressure control integrated into the panel.

The gun comes complete with a frame on which the gun can be set down. This frame is equipped with a controller for adjustment purposes and pressure gauge for reading off the extrusion pressure.

Different applicators work with different adhesive shapes. While FullTech Hotmelt Gun can be used with much more delivery forms, like granulates, pillows or even (big) blocks

FullTech Hotmelt Guns are characterised by their light weight and exceptional properties. These guns has few of advantages, these devices show perfect handling, reliability and excellent melting performance. Their ergonomic fit and long triggers ensure effortless work.

High standards for technology and handling. The hot melt adhesive is melted quickly and evenly with optimal melting performance.

The heated chamber melts adhesive within the gun and requires no heated hoses or tank.

FullTech Hotmelt Gun works with pressure sensitive adhesives and standard packaging hot melts of medium and low viscosities without solvents. (Adhesives can be purchased from Can Kimya A.Ş.)

FullTech Hot Melt Gun for Range of Applications

- Hot Melt Adhesives for Automobile Industry
- Working with Adhesives in the Construction Industry
- Hot Melt Adhesives for Display Production and Packaging
- Applications in the Furniture Industry
- Adhesives for Labelling
- Hot Melt Adhesives for Textile Industries
- Hot Melt Adhesives in the Electronic Industry
- Hot Melt Adhesives for Filter Industry
- Hot Melt Adhesives for Various Applications





FullTech Melting Tank

FullTech Melting Tank allows you to melt hotmelt adhesive products cleanly and economically.

You can melt and use all kinds of Hotmelt Adhesives in the form of granules and blocks.

This tank can be filled with approximately 2 kg of Hotmelt adhesive (Can be manufactured by increasing the capacity of the optional tank) and wait 20-30 minutes for it to melt after filling the tank.

This time depends on the properties and quantity of the Hotmelt Adhesive you will use.

To use the tank you need an air pressure .On the FullTech Melting Tank you can see the Filling button, the temperature setting indicator according to the Hotmelt melting point, On / Off buton, Filling-nozzle, and the Air pressure button

Hotmelt adhesives you want to use according to the characteristics of the melting tank can set up to 200C temperature.





Fax: +90 324 221 57 61

Mersin / TURKEY

e-Mail: info@tamtut.com

www.tamtut.com

Can Kimya manufactures, sells and services an extensive line of unique hot melt glue gun and hotmelt adhesives for all types of manufacturing applications. Our industrial hot melt glue equipment is used by manufacturing companies worldwide because it improves product quality with precise glue patterns, increases production with accelerated gluing capability and decreases costs with low cost bulk hot melt adhesive.